

TECHNICAL DATA SHEET



LINOFIX

Primer, a pigmented water-based acrylic fixative paint for indoor and outdoor use. It has a bright white color and high coverage. It is used to strengthen surfaces and enhance adhesion to all substrates. It keeps walls flat and absorbent.

Linofix is easy to work with. The material is suitable for all common mineral sub strates, fiber cement, wood materials, plasterboard, etc..



Technical Data

Binder base: acrylic copolymer

Pigment base: rutile titanium dioxide

Gloss level: matt

Color: white

Density: 1,29 g/cm³

Consumption: approx. 9-11 m² / kg depending on the surface

Processing temperature: + 5 ° C to max 35 ° C

Application tools: brush, roller or airless spray gun

Drying time: approx 4 - 6 hours (at + 20 ° C and 65% relative humidity)
reworkable after 12 hours

Tinting: with hm color mix

Dilution: ready to use, up to 10% water

VOC content: EU limit for this paint 30 g /L
Value for this paint 8.7 g /L

Storage: cool and frost-free, minimum 12 months in tightly closed original bucket

Features

- ✓ Excellent adherence
- ✓ Indoor & outdoor
- ✓ Environment friendly

Application

The substrate must be dry, free from dirt, dust, loose parts, oil, grease and other release agents.

Do not apply if there is a risk of rain or frost, direct sunlight and on highly heated surfaces.

Linofix is ready to use. Stir well before use.

Tools can be cleaned with water immediately after use.



EURL IN-HOUSE PAINTS
Ouled Slama, Blida, Algeria

P: +213 560 743 822

E: hm@inhousegroupe.com

W: www.inhousegroupe.com

facebook.com/sarl.gmdz

youtube.com/InHouseGroupDZ

+213 560 743 822