

TECHNICAL DATA SHEET



Matt 4407

Matt interior 4407 is a paint based on an aqueous acrylate for dull matt coatings on almost all interior surfaces. It is well covering, pleasant to work with, low odor and low emissions.

Matt interior 4407 is easy to work with. It is suitable for all interior walls and ceilings such as cement, plasterboards, wood materials... etc



Technical Data

Binder base: acrylic copolymer

Pigment base: rutile titanium dioxide

Gloss level: matt

Color: white

Density: 1,61 g/cm³

Wet abrasion resistance according to DIN EN 13300: Class 3

Contrast ratio: Class 2

Consumption: approx. 9-11 m² / kg depending on the surface

Processing temperature: + 5 ° C to max 35 ° C

Application tools: brush, roller or airless spray gun

Drying time: approx 4 - 6 hours (at + 20 ° C and 65% relative humidity)
reworkable after 12 hours

Tinting: with hm color mix

Dilution: ready to use, up to 10% water

Storage: cool and frost-free, minimum 12 months in tightly closed original bucket

Features

- ✓ Excellent opacity
- ✓ Low odor
- ✓ Environment friendly

Application

The substrate must be dry, free from dirt, dust, loose parts, oil, grease and other release agents.

Do not apply if there is a risk of rain or frost, direct sunlight and on highly heated surfaces.

Matt interior 4407 is ready to use. Stir well before use.

Tools can be cleaned with water immediately after use.



EURL IN-HOUSE PAINTS
Ouled Slama, Blida, Algeria

P: +213 560 743 822

E: hm@inhousegroupe.com

W: www.inhousegroupe.com

 facebook.com/sarl.gmdz

 youtube.com/InHouseGroupDZ

 +213 560 743 822